

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)


PCT

(10) International Publication Number
WO 2004/008182 A1

- (51) International Patent Classification⁷: **G01V 3/12, G07C 9/00, G08B 13/24**
- (21) International Application Number: **PCT/CA2003/001042**
- (22) International Filing Date: **11 July 2003 (11.07.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **60/395,124 12 July 2002 (12.07.2002) US**
- (71) Applicant (for all designated States except US): **PATH-MINDER INC. [CA/CA]; 51 Spectrum Way, Ottawa, Ontario K2R 1E6 (CA).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **PACHELL, John [CA/CA]; P.O. Box 1577, Carleton Place, Ontario K7C 4M3 (CA).**
- (74) Agents: **SMITH, Dallas, F. et al.; Gowling Lafleur Henderson LLP, 160 Elgin Street, Suite 2600, Ottawa, Ontario K1P 1C3 (CA).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**
- Published:
— with international search report

[Continued on next page]

(54) Title: **HUMAN DETECTION DEVICE**



(57) **Abstract:** A device for detecting humans includes a radio frequency transmitter for generating a signal in a frequency range in which human bodies absorb RF radiation. A radio frequency receiver is spaced relative to the radio frequency transmitter for receiving a portion of the signal. A human passageway is provided between the transmitter and receiver. The receiver includes a detector responsive to a change in the received portion of the signal for determining the passing by of a human. The detector is responsive to an amplitude and/or phase change in the received portion of the signal. A building access security system or people counting system would include a plurality of devices set up in adjacent lanes. The RF detection system may be augmented with the addition of an IR detection beam system, distance sensors and/or a video camera system. The video camera system may include stereo video.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.